NSN 5930-00-699-2053

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-699-2053

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.938 inches
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches
Overall Height: 1.553 inches
Overall Width:
0.688 inches
Body Length: 1.938 inches
Body Width:
0.688 inches
Body Height:
0.828 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.328 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.312 inches
Maximum Voltage Rating In Volts:
125.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Thread Size:
0.500 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
9.0 ounces
Switch Actuating Force:

13.0 ounces

NSN 5930-00-699-2053

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	Mov	ıρm	Δn	+
~	υιu	awı	IVIO	ven		ш.

Between 0.200 pretravel inches and 0.110 overtravel inches and 0.002 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

150.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0