

View Online at <https://aerobasegroup.com/nsn/5930-00-701-1113>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Driptight

**Housing Height:**

3.190 inches

**Housing Length:**

6.000 inches

**Housing Width:**

2.120 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.500 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

0.313 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 inch-ounces

**Switch Actuating Force:**

48.0 inch-ounces

**Actuator Movement:**

12.0 pretravel degrees and 60.0 overtravel degrees and 4.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0