

View Online at <https://aerobasegroup.com/nsn/5930-00-701-1113>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Driptight

Housing Height:

3.190 inches

Housing Length:

6.000 inches

Housing Width:

2.120 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.500 inches

Maximum Voltage Rating In Volts:

480.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

18

Thread Size:

0.313 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

48.0 inch-ounces

Actuator Movement:

12.0 pretravel degrees and 60.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0