

View Online at <https://aerobasegroup.com/nsn/5930-00-702-4111>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

2.761 inches

**Overall Height:**

1.000 inches

**Overall Width:**

1.000 inches

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.657 inches

**Body Length:**

0.980 inches

**Case Material:**

Metal

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.781 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.120 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0