

View Online at <https://aerobasegroup.com/nsn/5930-00-702-4692>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Body Diameter:**

0.660 inches

**Bushing Length:**

0.500 inches

**Body Length:**

0.940 inches

**Actuator Diameter:**

0.370 inches

**Actuator Height:**

0.370 inches

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.750 inches

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.000 amperes inductive dc and 1.500 amperes lamp dc

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0