## NSN 5930-00-702-6106

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-702-6106

#### **Thread Class:**

2b single pressure connection

#### **Overall Length:**

3.125 inches

## **Overall Height:**

1.834 inches

## **Overall Width:**

1.875 inches

#### Pressure Switch Type:

Differential

#### **Mounting Method:**

Flush

## Thready Qty Per Inch (tpi):

20 single pressure connection

#### **Contact Action Stimulus:**

Increase

Thread Size:

0.437 inches single pressure connection

## Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

#### Terminal Type:

Wire lead

## **Contact Load Current Rating:**

5.0 amperes resistive load single voltage

## **Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

## Contact Adjustment Range:

+50.00/+150.00 actuation point pounds per square inch and +70.00/+180.00 deactuation point pounds per square inch

## Contact Adjustment Type:

External deactuation point screw and external actuation point screw

## Contact Voltage Rating In Volts:

110.0 ac at sea level single voltage

#### **Pressure Connector Type:**

Flare, threaded internal single connection

#### Frequency In Hertz:

60.0 first voltage

## Media For Which Designed:

Gas or liquid

#### Style Designator:

Rectangular

#### **Thread Series Designator:**

Unf single pressure connection

# NSN 5930-00-702-6106

Pressure Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

