

View Online at <https://aerobasegroup.com/nsn/5930-00-702-6106>

Thread Class:

2b single pressure connection

Overall Length:

3.125 inches

Overall Height:

1.834 inches

Overall Width:

1.875 inches

Pressure Switch Type:

Differential

Mounting Method:

Flush

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.437 inches single pressure connection

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+50.00/+150.00 actuation point pounds per square inch and +70.00/+180.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

110.0 ac at sea level single voltage

Pressure Connector Type:

Flare, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0