

View Online at <https://aerobasegroup.com/nsn/5930-00-702-7115>

Inside Diameter:

0.250 inches single connection

Overall Length:

4.125 inches

Overall Width:

3.625 inches

Body Diameter:

3.000 inches

Body Length:

2.312 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

30.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

10.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.40/+30.00 actuation point inches of mercury and +0.40/+30.00 deactuation point inches of mercury

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

0.50 actuation point inches of mercury and 31.40 actuation point inches of mercury and 0.10 differential point inches of mercury and 1.40 differential point inches of mercury

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Pressure Connector Type:

Swivel nut, compression, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0