NSN 5930-00-705-0891

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-705-0891

Overall Length:

4.188 inches

Body Diameter:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Distance Between Mounting Facility Centers:

2.250 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

70.00 actuation point pounds per square inch and 50.00 deactuation point pounds per square inch and 20.00 differential point pound

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas

NSN 5930-00-705-0891

Pressure Switch - Page 2 of 2



Style Designator:
Cylindrical
Thread Series Designator:
Unc single pressure connection
Shelf Life:
N/a

Unit Of Measure:

Demilitarization:

No Fiig:

A048b0