NSN 5930-00-705-2884

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-705-2884

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.093 inches

Overall Width:

0.687 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.040 inches

Case Material:

Case Male

Plastic

Unthreaded Mounting Hole Diameter:

0.139 inches

Actuator Style:

Roller arm

Actuator Height:

0.843 inches

Actuator Roller Diameter:

0.110 inches

Actuator Roller Width:

0.170 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.25 ounces

Switch Actuating Force:

2.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

NSN 5930-00-705-2884

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0