

View Online at <https://aerobasegroup.com/nsn/5930-00-705-4314>

**Body Style:**

Hole mounted

**Overall Length:**

Between 0.610 inches and 0.640 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.370 inches and 0.380 inches

**Overall Height:**

0.824 inches

**Overall Width:**

Between 0.222 inches and 0.242 inches

**Body Length:**

Between 0.610 inches and 0.640 inches

**Body Width:**

Between 0.222 inches and 0.242 inches

**Body Height:**

Between 0.240 inches and 0.260 inches

**Unthreaded Mounting Hole Diameter:**

0.076 inches

**Actuator Length:**

0.594 inches

**Actuator Style:**

Leaf

**Actuator Width:**

Between 0.120 inches and 0.130 inches

**Actuator Free Position Height:**

Between 0.350 inches and 0.385 inches

**Maximum Voltage Rating In Volts:**

125.0 ac

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

Between 2.0 ounces and 5.0 ounces

**Actuator Movement:**

0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0