NSN 5930-00-705-4314

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-705-4314

Body Style:	
Hole mounted	
Overall Length:	
Between 0.610 inches and 0.640 inches	
Center To Center Distance Between Mounting Facilities Parallel To	Length:
Between 0.370 inches and 0.380 inches	
Overall Height:	
0.824 inches	
Overall Width:	
Between 0.222 inches and 0.242 inches	
Body Length:	
Between 0.610 inches and 0.640 inches	
Body Width:	
Between 0.222 inches and 0.242 inches	
Body Height:	
Between 0.240 inches and 0.260 inches	
Unthreaded Mounting Hole Diameter:	
0.076 inches	
Actuator Length:	
0.594 inches	
Actuator Style:	
Leaf	
Actuator Width:	
Between 0.120 inches and 0.130 inches	
Actuator Free Position Height:	
Between 0.350 inches and 0.385 inches	
Maximum Voltage Rating In Volts:	
125.0 ac	
Inclosure Type:	
Uninclosed	
Mounting Method:	
Unthreaded hole	
Features Provided:	
Actuator seal	
Nonpile-up Contact Arrangement:	
1 pole, double throw, one position momentary single switch unit	
Switch Release Force:	
1.0 ounces	
Switch Actuating Force:	

Actuator Movement:

Between 2.0 ounces and 5.0 ounces

0.030 differential inches

NSN 5930-00-705-4314

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:	Contact Load	Current Rating	At Maximum	Rated Voltage:
---	--------------	-----------------------	------------	----------------

3.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0