

View Online at <https://aerobasegroup.com/nsn/5930-00-706-3391>

Thread Class:

3a single pressure connection

Overall Length:

2.500 inches

Overall Diameter:

0.710 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Temperature Rating:

125.0 degrees celsius

Mounting Method:

Inlet connection

Features Provided:

Electrical access port and hermetically sealed case

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

250.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

500.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

250.0 milliamperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

130.00 actuation point pounds per square inch gage and 2.00 deactuation point pounds per square inch gage and 128.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0