# NSN 5930-00-706-8334

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-706-8334

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

1.938 inches

### **Overall Height:**

1.875 inches

#### **Overall Width:**

1.625 inches

#### Shaft Diameter:

0.250 inches single actuator

### Shaft Length:

1.000 inches single actuator

#### **Nonturn Device Radius:**

## 0.531 inches at 4: 30 o'clock

### Individual Section Quantity:

1

Nonturn Device Type:

Tab at 4: 30 o'clock

### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

5 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

### **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

# **Precious Material And Location:**

Clips and rotor blades silver

# NSN 5930-00-706-8334

Rotary Switch - Page 2 of 2

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

