NSN 5930-00-708-3589

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-708-3589

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.531 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
5.688 inches
Overall Width:
0.969 inches
Body Length:
1.625 inches
Body Width:
0.812 inches
Body Height:
2.531 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Style:
Round
Actuator Diameter:
0.190 inches
Actuator Height:
0.350 inches
Actuator Adapter Style:
Pushbutton
Adapter Bushing Length:
3.750 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-00-708-3589 Sensitive Switch - Page 2 of 2



Switch Release Force:
4.0 ounces
Switch Actuating Force:
12.0 ounces
Actuator Movement:
Between 0.815 pretravel inches and 0.781 overtravel inches and 0.250 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0