

View Online at <https://aerobasegroup.com/nsn/5930-00-708-6671>

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Overall Length:

2.063 inches

First Flat Length:

0.469 inches single actuator

Flat Height:

0.182 inches single actuator and 0.192 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.249 inches single actuator

Shaft Length:

0.500 inches single actuator

Overall Diameter:

1.875 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.0 amperes lamp load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0