NSN 5930-00-708-8649

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-708-8649

Body Style:

Bushing mounted

Overall Length:

2.761 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.781 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.120 inches

Housing Diameter:

1.000 inches

Housing Length:

0.980 inches

Housing Bushing Length:

0.657 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire lead

NSN 5930-00-708-8649

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

