NSN 5930-00-708-8649

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-708-8649

view Online at https://aerobasegroup.com/nsn/5930-00-706-6649
Body Style:
Bushing mounted
Overall Length:
2.761 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.781 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.120 inches
Housing Diameter:
1.000 inches
Housing Length:
0.980 inches
Housing Bushing Length:
0.657 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
64.0 ounces
Switch Actuating Force:
Between 96.0 ounces and 192.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000
amperes inductive ac
Thread Series Designator:
Unef
Terminal Type And Quantity:

6 wire lead

NSN 5930-00-708-8649

Sensitive Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0