

View Online at <https://aerobasegroup.com/nsn/5930-00-708-8665>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility and 0.385 inches single mounting facility

**Overall Length:**

Between 2.995 inches and 3.005 inches

**First Flat Length:**

0.375 inches single actuator and 0.385 inches single actuator

**Flat Height:**

0.216 inches single actuator and 0.220 inches single actuator

**Shaft Diameter:**

0.240 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.495 inches single actuator and 0.505 inches single actuator

**Overall Diameter:**

Between 1.240 inches and 1.260 inches

**Nonturn Device Radius:**

0.525 inches at 3: 00 o'clock and 0.535 inches at 3: 00 o'clock

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 each section rear

**Throw Quantity:**

6 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts and rotor blades silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0