## NSN 5930-00-708-9399

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-708-9399

**Thread Class:** 

2b single pressure connection

Thread Length:

0.438 inches single pressure connection

**Hazardous Locations/environmental Protection:** 

Dustproof and watertight

**Overall Length:** 

5.000 inches

**Overall Height:** 

5.938 inches

Overall Width:

2.688 inches

**Body Length:** 

2.750 inches

**Body Height:** 

2.688 inches

**Intermediate Horizontal Distance Between Mounting Centers:** 

1.203 inches

**Longest Vertical Distance Between Mounting Centers:** 

3.281 inches

**Pressure Switch Type:** 

Gage

**Mounting Method:** 

Flange

Thready Qty Per Inch (tpi):

20 single pressure connection

**Contact Action Stimulus:** 

Increase

Thread Size:

0.4375 inches single pressure connection

**Mounting Facility Pattern:** 

Obtuse triangle

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally open, momentary action

**Terminal Type:** 

Tab w/screw

**Contact Load Current Rating:** 

9.6 amperes resistive load fourth voltage

**Contact Adjustability:** 

Deactuation point not adjustable, manual reset and actuation point adjustable

**Contact Adjustment Range:** 

+4.00/+35.00 actuation point pounds per square inch

## NSN 5930-00-708-9399

Pressure Switch - Page 2 of 2



Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A048b0