NSN 5930-00-708-9399

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-708-9399

Thread Class:

2b single pressure connection

Thread Length:

0.438 inches single pressure connection

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

5.000 inches

Overall Height:

5.938 inches

Overall Width:

2.688 inches

Body Length:

2.750 inches

Body Height:

2.688 inches

Intermediate Horizontal Distance Between Mounting Centers:

1.203 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.4375 inches single pressure connection

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point not adjustable, manual reset and actuation point adjustable

Contact Adjustment Range:

+4.00/+35.00 actuation point pounds per square inch

NSN 5930-00-708-9399

Pressure Switch - Page 2 of 2



Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level third voltage
Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A048b0