

View Online at <https://aerobasegroup.com/nsn/5930-00-708-9694>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.250 inches

Overall Height:

3.812 inches

Overall Width:

3.812 inches

First Flat Length:

1.000 inches single actuator

Flat Height:

0.250 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.500 inches single actuator

Unthreaded Mounting Hole Diameter:

0.250 inches single mounting facility

Individual Section Quantity:

2

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

74089-3

Longest Horizontal Distance Between Mounting Centers:

3.219 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.219 inches single mounting facility

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

8 each section front

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

230.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

89661-331c113h01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0