## NSN 5930-00-708-9694

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-708-9694

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
3.250 inches
Overall Height:
3.812 inches
Overall Width:
3.812 inches
First Flat Length:
1.000 inches single actuator
Flat Height:
0.250 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.500 inches single actuator
Unthreaded Mounting Hole Diameter:
0.250 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
74089-3
Longest Horizontal Distance Between Mounting Centers:
3.219 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.219 inches single mounting facility
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
8 each section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:

230.0 ac at sea level

## NSN 5930-00-708-9694

Rotary Switch - Page 2 of 2

A052b0



Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
30.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Test Data Document:
89661-331c113h01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: