## NSN 5930-00-709-2037

Rotary Switch - Page 1 of 2

**Thread Class:** 

Overall Length:

2b single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-709-2037

| 2.907 inches                                 |
|--|
| Overall Height:                              |
| 2.500 inches                                 |
| Overall Width:                               |
| 2.500 inches                                 |
| First Flat Length:                           |
| 0.438 inches single actuator                 |
| Flat Height:                                 |
| 0.219 inches single actuator                 |
| Shaft Diameter:                              |
| 0.250 inches single actuator                 |
| Shaft Length:                                |
| 0.688 inches single actuator                 |
| Unthreaded Mounting Hole Diameter:           |
| 0.312 inches single mounting facility        |
| Individual Section Quantity:                 |
| 4  |
| Knob Manufacturer Code:                      |
| 82121  |
| Knob Manufacturer Part Number:               |
| A  |
| Switch Contact Basic Design:                 |
| Nonpile-up symmetrical                       |
| Pole Quantity:                               |
| 1 each section front                         |
| Throw Quantity:                              |
| 3 each section front                         |
| Mounting Facility Circle Radius:             |
| 0.250 inches single mounting facility        |
| Mounting Method:                             |
| Bracket single mounting facility             |
| Features Provided:                           |
| Actuator knob                                |
| Thready Qty Per Inch (tpi):                  |
| 24 single mounting facility                  |
| Thread Size:                                 |
| 0.190 inches single mounting facility        |
| Contact Voltage Rating In Volts:             |
| 450.0 highest ac voltage rating at sea level |
|  |

## NSN 5930-00-709-2037

Rotary Switch - Page 2 of 2

A052b0



| Mounting Facility Pattern:   |
|--|
| Four position circular single mounting facility  |
| Switch Actuator Indexing Position Quantity:  |
| 3 single actuator  |
| Shaft Type:  |
| Round, flatted, threaded hole single actuator  |
| Terminal Type:   |
| Tab w/screw  |
| Contact Switching Action:  |
| Breaks before makes each section front   |
| Switch Actuator Positioning Increment:   |
| 90.0 degrees single actuator   |
| Switch Actuator Stop Device Type:  |
| Fixed stop single actuator   |
| Contact Load Current Rating:   |
| 5.0 amperes resistive load highest dc voltage rating at sea level  |
| Style Designator:  |
| Tap, circuit selector  |
| Test Data Document:  |
| 89661-54b7064h02 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                    |
| Thread Series Designator:  |
| Unc single mounting facility   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |