

View Online at <https://aerobasegroup.com/nsn/5930-00-709-2037>

Thread Class:

2b single mounting facility

Overall Length:

2.907 inches

Overall Height:

2.500 inches

Overall Width:

2.500 inches

First Flat Length:

0.438 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.688 inches single actuator

Unthreaded Mounting Hole Diameter:

0.312 inches single mounting facility

Individual Section Quantity:

4

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

A

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section front

Mounting Facility Circle Radius:

0.250 inches single mounting facility

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

450.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest dc voltage rating at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

89661-54b7064h02 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0