## NSN 5930-00-710-1920

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-710-1920

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|---|
| 1.000 inches  |
| Body Length:  |
| 1.200 inches  |
| Body Height:  |
| 0.825 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.094 inches  |
| Actuator Length:  |
| 1.812 inches  |
| Actuator Style:   |
| Leaf  |
| Actuator Width:   |
| 0.375 inches  |
| Maximum Voltage Rating In Volts:  |
| 115.0 ac  |
| Mounting Method:  |
| Unthreaded hole   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary single switch unit           |
| Switch Actuating Force:   |
| 2.5 grams   |
| Actuator Movement:  |
| 0.500 differential inches   |
| Contact Load Current Rating At Maximum Rated Voltage:                     |
| 3.000 amperes resistive ac  |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A053a0  |
|   |