

View Online at <https://aerobasegroup.com/nsn/5930-00-710-9533>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.312 inches

Outside Diameter:

0.125 inches single connection

Overall Height:

1.094 inches

Overall Width:

1.125 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 257.0 degrees fahrenheit

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

18.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

35.00 pounds per square inch

Terminal Type:

Turret

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

11.50 actuation point pounds per square inch absolute and 9.50 deactuation point pounds per square inch absolute and 2.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0