

View Online at <https://aerobasegroup.com/nsn/5930-00-710-9533>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

1.312 inches

**Outside Diameter:**

0.125 inches single connection

**Overall Height:**

1.094 inches

**Overall Width:**

1.125 inches

**Pressure Switch Type:**

Absolute

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 257.0 degrees fahrenheit

**Mounting Method:**

Inlet connection

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

18.00 pounds per square inch

**Thread Size:**

0.125 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

35.00 pounds per square inch

**Terminal Type:**

Turret

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

11.50 actuation point pounds per square inch absolute and 9.50 deactuation point pounds per square inch absolute and 2.00 differential point pounds per square inch absolute

**Contact Voltage Rating In Volts:**

30.0 dc at sea level second voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0