## NSN 5930-00-711-1807

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-711-1807

**Thread Class:** 

2a single pressure connection

**Overall Length:** 

4.156 inches

**Outside Diameter:** 

0.625 inches single connection

**Overall Height:** 

1.500 inches

**Overall Width:** 

1.500 inches

**Body Length:** 

2.115 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.209 inches and 0.214 inches

**Distance Between Mounting Facility Centers:** 

1.125 inches

**Pressure Switch Type:** 

Gage

**Operating Tempurature Rating:** 

Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit

**Mounting Method:** 

Line and threaded hole

**Contact Action Stimulus:** 

Increase

**Proof Pressure:** 

300.00 pounds per square inch gage

Thread Size:

0.625 inches single pressure connection

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Connector, receptacle

**Contact Load Current Rating:** 

2.0 amperes resistive load single voltage

**Contact Adjustability:** 

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:** 

250.00 actuation point pounds per square inch gage and 270.00 actuation point pounds per square inch gage and 220.00 deactuation point pounds per square inch gage and 240.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level single voltage

## **NSN 5930-00-711-1807**Pressure Switch - Page 2 of 2



Pressure Connector Type:
Flared, threaded external single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unef single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0