

View Online at <https://aerobasegroup.com/nsn/5930-00-711-8600>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.500 inches

Overall Height:

1.875 inches

Overall Width:

1.750 inches

First Flat Length:

0.875 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.875 inches single actuator

Nonturn Device Radius:

0.531 inches at 10: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 10: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

2 1st section front

Throw Quantity:

3 1st section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 highest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0