

View Online at <https://aerobasegroup.com/nsn/5930-00-713-4188>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

7.688 inches

**Overall Height:**

6.000 inches

**Overall Width:**

4.750 inches

**First Flat Length:**

1.125 inches single actuator

**Flat Height:**

0.312 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.750 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.406 inches single mounting facility

**Individual Section Quantity:**

5

**Knob Manufacturer Code:**

10001

**Knob Manufacturer Part Number:**

900056202-74095-1

**Longest Horizontal Distance Between Mounting Centers:**

3.750 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.250 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

2 each section rear

**Mounting Method:**

Base single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

60.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0