## NSN 5930-00-715-9456

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-715-9456

| view Offiline at https://derobasegroup.com/nish/0000-00-7 10-0400 |
|---|
| Thread Class:   |
| 2b single mounting facility                                       |
| Overall Length:   |
| 3.125 inches  |
| Overall Height:   |
| 2.812 inches  |
| Overall Width:  |
| 2.812 inches  |
| First Flat Length:  |
| 0.438 inches single actuator                                      |
| Flat Height:  |
| 0.218 inches single actuator                                      |
| Shaft Diameter:   |
| 0.250 inches single actuator                                      |
| Shaft Length:   |
| 0.688 inches single actuator                                      |
| Individual Section Quantity:                                      |
| 1   |
| Knob Manufacturer Code:   |
| 82121   |
| Longest Horizontal Distance Between Mounting Centers:             |
| 2.297 inches single mounting facility                             |
| Longest Vertical Distance Between Mounting Centers:               |
| 2.297 inches single mounting facility                             |
| Switch Contact Basic Design:                                      |
| Nonpile-up symmetrical  |
| Pole Quantity:  |
| 1 single section front  |
| Throw Quantity:   |
| 6 single section front  |
| Mounting Method:  |
| Flange single mounting facility                                   |
| Features Provided:  |
| Actuator knob   |
| Thready Qty Per Inch (tpi):                                       |
| 24 single mounting facility                                       |
| Thread Size:  |
| 0.190 inches single mounting facility                             |
| Contact Voltage Rating In Volts:                                  |

125.0 ac at sea level

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility

## NSN 5930-00-715-9456

Rotary Switch - Page 2 of 2



## **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks single section front **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Contact Load Current Rating:** 10.0 amperes resistive load ac at sea level **Style Designator:** Tap, square frame **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A052b0