NSN 5930-00-715-9456

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-715-9456

view Offiline at https://derobasegroup.com/nish/0000-00-7 10-0400
Thread Class:
2b single mounting facility
Overall Length:
3.125 inches
Overall Height:
2.812 inches
Overall Width:
2.812 inches
First Flat Length:
0.438 inches single actuator
Flat Height:
0.218 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.688 inches single actuator
Individual Section Quantity:
1
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
2.297 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.297 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section front
Throw Quantity:
6 single section front
Mounting Method:
Flange single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

NSN 5930-00-715-9456

Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity: 6 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks single section front **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Contact Load Current Rating:** 10.0 amperes resistive load ac at sea level **Style Designator:** Tap, square frame **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A052b0