NSN 5930-00-716-5276

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-716-5276

Overall Length:
0.510 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.281 inches
Overall Height:
0.535 inches
Overall Width:
0.200 inches
Body Length:
0.510 inches
Body Width:
0.200 inches
Body Height:
0.350 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.093 inches
Actuator Free Position Height:
0.355 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Uninclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, double break, momentary action single switch unit
Switch Release Force:
1.5 ounces
Switch Actuating Force:
Between 3.0 ounces and 8.0 ounces
Actuator Movement:

Contact Load Current Rating At Maximum Rated Voltage:

Between 0.035 pretravel inches and 0.006 overtravel inches and 0.015 differential inches

8.000 amperes resistive dc and 5.000 amperes inductive dc and 8.000 amperes resistive ac and 5.000 amperes inductive ac

NSN 5930-00-716-5276 Sensitive Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0