

View Online at <https://aerobasegroup.com/nsn/5930-00-716-5276>

Body Style:

Hole mounted

Overall Length:

0.510 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.281 inches

Overall Height:

0.535 inches

Overall Width:

0.200 inches

Body Length:

0.510 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.093 inches

Actuator Free Position Height:

0.355 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action single switch unit

Switch Release Force:

1.5 ounces

Switch Actuating Force:

Between 3.0 ounces and 8.0 ounces

Actuator Movement:

Between 0.035 pretravel inches and 0.006 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

8.000 amperes resistive dc and 5.000 amperes inductive dc and 8.000 amperes resistive ac and 5.000 amperes inductive ac

Precious Material And Location:

Contact surfaces gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0