

View Online at <https://aerobasegroup.com/nsn/5930-00-717-1378>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.225 inches single mounting facility and 0.275 inches single mounting facility

**Overall Length:**

2.890 inches

**First Flat Length:**

0.484 inches single actuator and 0.516 inches single actuator

**Flat Height:**

0.214 inches single actuator and 0.224 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.484 inches single actuator and 0.516 inches single actuator

**Overall Diameter:**

Between 0.985 inches and 1.015 inches

**Individual Section Quantity:**

4

**End Application:**

Aircraft, viking s-3b, helicopter, seasprite h-2, fms - aircraft, orion p-3, helicopter, sea king h-3, helicopter, lamps mark iii, sh-60b, aircraft, orion p-3

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

8 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

115.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0