

View Online at <https://aerobasegroup.com/nsn/5930-00-717-1378>

Thread Class:

2a single mounting facility

Thread Length:

0.225 inches single mounting facility and 0.275 inches single mounting facility

Overall Length:

2.890 inches

First Flat Length:

0.484 inches single actuator and 0.516 inches single actuator

Flat Height:

0.214 inches single actuator and 0.224 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.484 inches single actuator and 0.516 inches single actuator

Overall Diameter:

Between 0.985 inches and 1.015 inches

Individual Section Quantity:

4

End Application:

Aircraft, viking s-3b, helicopter, seasprite h-2, fms - aircraft, orion p-3, helicopter, sea king h-3, helicopter, lamps mark iii, sh-60b, aircraft, orion p-3

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

8 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0