

View Online at <https://aerobasegroup.com/nsn/5930-00-721-0028>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Height:**

3.060 inches

**Overall Width:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.172 inches 2nd mounting facility

**Individual Section Quantity:**

11

**Longest Horizontal Distance Between Mounting Centers:**

2.500 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

8 each section rear

**Mounting Method:**

Bracket 1st mounting facility and unthreaded hole 1st mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Rotor Through Connection Quantity:**

1 each section

**Mounting Facility Pattern:**

Two position in-line 1st mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks 2nd section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Special Features:**

W/integral solenoid

**Precious Material And Location:**

Contacts and rotor surface silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0