

View Online at <https://aerobasegroup.com/nsn/5930-00-721-0028>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Height:

3.060 inches

Overall Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.172 inches 2nd mounting facility

Individual Section Quantity:

11

Longest Horizontal Distance Between Mounting Centers:

2.500 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

8 each section rear

Mounting Method:

Bracket 1st mounting facility and unthreaded hole 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Two position in-line 1st mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks 2nd section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

W/integral solenoid

Precious Material And Location:

Contacts and rotor surface silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0