NSN 5930-00-721-2677

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-721-2677

#### **Thread Class:**

2b single mounting facility

#### **Overall Length:**

6.937 inches

# **Overall Height:**

3.312 inches

## **Overall Width:**

2.875 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

1.562 inches single actuator

#### **Distance Between Mounting Facility Centers:**

2.875 inches single mounting facility

#### **Individual Section Quantity:**

3

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

## Throw Quantity:

4 each section rear

## Mounting Method:

Threaded hole single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.164 inches single mounting facility

## Contact Voltage Rating In Volts:

400.0 ac at sea level

## **Mounting Facility Pattern:**

Two position in-line single mounting facility

## Switch Actuator Indexing Position Quantity:

4 single actuator

## Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Breaks before makes each section rear

# Switch Actuator Positioning Increment:

90.0 degrees single actuator

# NSN 5930-00-721-2677

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

20.0 amperes resistive load ac at sea level

#### **Precious Material And Location:**

Terminal surfaces and contacts silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, panel mount

## Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0