## NSN 5930-00-721-2768

Push Switch - Page 1 of 2

12 turret and 5 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5930-00-721-2768

**Body Style:** Panel mount **Overall Length:** 1.210 inches **Overall Height:** 3.022 inches **Overall Width:** Between 0.950 inches and 0.970 inches **Body Length:** 1.200 inches **Body Width:** Between 0.950 inches and 0.970 inches **Body Height:** 2.812 inches **Case Material:** Metal Actuator Length: Between 1.020 inches and 1.050 inches **Actuator Style:** Rectangular **Actuator Height:** Between 0.164 inches and 0.210 inches Actuator Width: Between 0.720 inches and 0.750 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** White single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac **Precious Material And Location:** Contacts silver **Terminal Type And Quantity:** 

## NSN 5930-00-721-2768

Push Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

