

View Online at <https://aerobasegroup.com/nsn/5930-00-721-3788>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.250 inches

Body Length:

0.525 inches

Body Width:

0.525 inches

Body Height:

0.410 inches

Actuator Style:

Round

Actuator Diameter:

0.140 inches

Actuator Height:

0.156 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0