

View Online at <https://aerobasegroup.com/nsn/5930-00-722-0252>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.171 inches

Overall Height:

0.337 inches

Body Diameter:

0.650 inches

Body Height:

Between 0.315 inches and 0.319 inches

Unthreaded Mounting Hole Diameter:

0.104 inches

Distance Between Mounting Facility Centers:

Between 0.932 inches and 0.942 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -80.0 degrees fahrenheit and 270.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

4.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

68.00 actuation point degrees fahrenheit and 63.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0