

View Online at <https://aerobasegroup.com/nsn/5930-00-723-4775>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Diameter:**

1.000 inches

**Bushing Length:**

Between 0.455 inches and 0.485 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.225 inches and 0.255 inches

**Actuator Height:**

Between 0.675 inches and 0.705 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc

**Mounting Surface To Terminal End Distance:**

1.750 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Holding solenoid

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

**Special Features:**

Two terminals for solenoid

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

5 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0