

View Online at <https://aerobasegroup.com/nsn/5930-00-723-4775>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Body Diameter:

1.000 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.225 inches and 0.255 inches

Actuator Height:

Between 0.675 inches and 0.705 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

1.750 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

Special Features:

Two terminals for solenoid

Thread Series Designator:

Uns

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0