## NSN 5930-00-723-7697

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-723-7697

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

## **Overall Length:**

1.563 inches

## **Overall Height:**

1.093 inches

#### **Overall Width:**

0.953 inches

#### Shaft Diameter:

0.125 inches single actuator

## Shaft Length:

0.688 inches single actuator

## **Nonturn Device Radius:**

## 0.375 inches at 3: 00 o'clock

## Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section rear

## **Throw Quantity:**

5 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.250 inches single mounting facility

## Contact Voltage Rating In Volts:

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

5 single actuator

## Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-723-7697

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0