

View Online at <https://aerobasegroup.com/nsn/5930-00-724-6030>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.312 inches

**Body Length:**

0.500 inches

**Body Width:**

0.250 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.125 inches

**Actuator Height:**

0.375 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.484 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0