

View Online at <https://aerobasegroup.com/nsn/5930-00-725-2080>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.995 inches and 1.005 inches

**Body Length:**

Between 1.925 inches and 1.955 inches

**Body Width:**

Between 0.677 inches and 0.697 inches

**Body Height:**

Between 1.025 inches and 1.055 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Length:**

0.030 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

1.484 inches

**Actuator Width:**

0.160 inches

**Actuator Free Position Height:**

0.670 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Aircraft phantom f-4

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, double break/double make, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 16.0 ounces and 26.0 ounces

**Actuator Movement:**

0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 2.500 amperes motor ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

**Terminal Type And Quantity:**

5 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0