

View Online at <https://aerobasegroup.com/nsn/5930-00-725-5152>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.810 inches

**Body Length:**

2.910 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

0.780 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.120 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

1.000 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 inch-ounces

**Switch Actuating Force:**

Between 96.0 inch-ounces and 192.0 inch-ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0