

View Online at <https://aerobasegroup.com/nsn/5930-00-726-2631>

Overall Length:

4.562 inches

Overall Height:

8.281 inches

Overall Width:

3.688 inches

Body Length:

4.562 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.000 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Calibrated scale

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

9000.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

30.0 milliamperes inductive load third voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+50.00/+6000.00 actuation point pounds per square inch and +50.00/+6000.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw with scale

Contact Stimulus Rating:

20.00 actuation point pounds per square inch and 15.00 deactuation point pounds per square inch and 5.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

6.0 dc at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0